

Spectrabind Vertical

Type Aliphatic (UV Stable) 3 part system

Form Supplied Spectrabind Vertical is supplied in a 1.8kg Kit. (0.9kg of each A & B) along with a small

amount of catalyst and a syringe.

Uses As a primer for coved skirts and as a binding agent for laying resin bound and stone

carpet material vertically.

Product Description

Spectrabind Vertical has been specially developed to allow steps to be totally clad with Resin Bound aggregate. It is an extremely thixotropic version of our market leading Spectrabind Clear Resin. It is vrtuaally water white when died. It is also UV stable and won't discolor with age.

Coverage

One kit will cover approx 1 sqm or 5 linear meters (assuming average step of 200mm)

Product Application

- 1. Thoroughly mix SPECTRABIND VERTICAL Part B into the SPECTRABIND VERTICAL Part A.
- 2. Add 10-15 ml of Stone Carpet Catalyst using the syringe provided and mix well.
- 3. Quickly apply a liberal coat of the mixed A/B to the vertical surface for use as a primer. This is typically 0.5kg or just over a quarter of the mix.
- 4. Add the remaining resin ca 12.5kg of 1-3mm aggregate and mix until all the stones are evenly coated. This is based on natural aggregate which is relatively dusty and you will probably need to add less if using a coloured quartz or similar non-dusty aggregate. The maximum recommended aggregate size is 2-3mm.
- 5. Trowel the stone carpet onto the vertical surface whilst the primer is still wet. Ensure even and flat coverage at a depth of 5-6mm. If the resin is not going off fast enough (ie in cold conditions) add 5ml more catalyst.

Storage

Store out of direct sunlight in a humidity-controlled atmosphere, at 10-20°C. Too warm and the resin can become too runny and will lose its vertical effectiveness. Too cold and the resin can become thick and unworkable. Moisture (including moist air) will initiate the cure of Spectrabind Verical Part B in part used containers, even if resealed, unless they are purged with dry nitrogen. Wherever possible, store in original unopened containers until needed. Shelf life is 6 months from date of manufacture.

Safety Information

Please refer to the Material Safety Data Sheet corresponding to these products. Precautions must be taken to ensure good ventilation and to prevent direct contact with skin and eyes. May cause sensitisation in some cases.

*Note: Any and all information or suggestions/recommendations provided by Spectrum Chemicals Ltd. regarding the application of products supplied by the company, be this in the form of technical literature, or in correspondence relating to specific queries, or otherwise, is based on data believed to be reliable, however it is for the customer to decide for itself the suitability of the product for their own particular use, based on their requisite skills and know-how within the industry, and it is therefore deemed by the company that the customer will have done so at their sole discretion and risk. No liability will be accepted by Spectrum Chemicals Ltd should materials or methods prove to be unsuitable for any application.

Rev. 1.0 10.17



Spectrum Chemicals Limited

Doddington Road, Wollaston, Northamptonshire NN29 7PR T +44 (0)1933 664141 F +44 (0)1933 663758 sales@spectrumchemicals.co.uk www.spectrumchemicals.co.uk





